

View Online at <https://aerobasegroup.com/nsn/5940-00-836-7672>

**Dielectric Withstanding Voltage In Volts:**

1.5

**Body Style:**

Barrier type

**Mounting Slot Length:**

0.187 inches

**Mounting Slot Width:**

0.150 inches

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.312 inches

**Distance Between Terminal Row Centers:**

0.375 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.062 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.344 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.156 inches

**Boardlength:**

1.375 inches

**Boardwidth:**

0.688 inches

**Boardheight:**

0.469 inches

**Board Height Excluding Terminals:**

0.375 inches

**Base Thickness:**

0.250 inches

**Current Rating In Amps:**

20.0

**Mounting Facility Type And Quantity:**

2 slot

**Terminal Connecting Link Quantity:**

2 single

**Nonfeedthru Terminal Type:**

600 single

**Terminal Connecting Link Type:**

1 single

**Nonfeedthru Terminal Quantity:**

2 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Nonfeedthru

**Material:**

Plastic polyester board and glass fiber board

**Material Specification:**

Qq-b728, class b federal specification single material response terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0

**Mil-std (military Standard):**

Mil-m-14 spec.