

View Online at <https://aerobasegroup.com/nsn/5940-00-837-2229>

Mounting Hole Diameter:

0.160 inches

Dielectric Withstanding Voltage In Volts:

1100.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.380 inches

Distance Between Terminal Row Centers:

0.312 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.312 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.189 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.140 inches

Boardlength:

2.910 inches

Boardwidth:

0.880 inches

Boardheight:

0.410 inches

Board Height Excluding Terminals:

0.410 inches

Base Thickness:

0.250 inches

Current Rating In Amps:

15.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

6 single

Nonfeedthru Terminal Type:

857 single

Criticality Code Justification:

Test

Terminal Connecting Link Type:

1 single

Nonfeedthru Terminal Quantity:

6 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Material:

Plastic diallyl phthalate board and silica board

Material Specification:

Mil-m-14, type mdg military specification single material response board

Surface Treatment:

Nickel terminals

Test Data Document:

10001-2547256 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.