

View Online at <https://aerobasegroup.com/nsn/5940-00-837-8044>

Dielectric Withstanding Voltage In Volts:

2.2

Body Style:

Barrier type

Mounting Slot Length:

0.218 inches

Mounting Slot Width:

0.173 inches

Terminal Row Quantity:

1

Center To Center Distance Between Terminals:

0.375 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.125 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.312 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.281 inches

Boardlength:

4.625 inches

Boardwidth:

0.625 inches

Boardheight:

1.125 inches

Board Height Excluding Terminals:

1.000 inches

Base Thickness:

0.500 inches

Current Rating In Amps:

40.0

Mounting Facility Type And Quantity:

2 slot

Feedthru Connection End Type:

598 fourth combination both ends

Feedthru Terminal Quantity:

9 single combination

Terminal Pattern Arrangement:

Single row

Terminal Design:

Vertical feedthru

Special Markings:

1 through 9

Material:

Plastic polyester board and glass fiber board

Material Specification:

Qq-b728, class b federal specification single material response terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.