

View Online at <https://aerobasegroup.com/nsn/5940-00-901-2683>

**Dielectric Withstanding Voltage In Volts:**

2200.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

1

**Center To Center Distance Between Terminals:**

0.375 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.875 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.312 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.250 inches

**Boardlength:**

3.375 inches

**Boardwidth:**

0.625 inches

**Boardheight:**

1.000 inches

**Board Height Excluding Terminals:**

0.500 inches

**Base Thickness:**

0.500 inches

**Current Rating In Amps:**

40.0

**Mounting Facility Type And Quantity:**

2 slot

**Feedthru Connection End Type:**

600 both ends single combination

**Feedthru Terminal Quantity:**

6 single combination

**Terminal Pattern Arrangement:**

Single row

**Terminal Design:**

Vertical feedthru

**Material:**

Plastic polyester board and glass fiber board

**Material Specification:**

Mil-m-14, type mai-60 military specification single material response board

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0

**Mil-std (military Standard):**

Mil-m-14 spec.