

View Online at <https://aerobasegroup.com/nsn/5940-00-901-2683>

Dielectric Withstanding Voltage In Volts:

2200.0

Body Style:

Barrier type

Terminal Row Quantity:

1

Center To Center Distance Between Terminals:

0.375 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.875 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.312 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.250 inches

Boardlength:

3.375 inches

Boardwidth:

0.625 inches

Boardheight:

1.000 inches

Board Height Excluding Terminals:

0.500 inches

Base Thickness:

0.500 inches

Current Rating In Amps:

40.0

Mounting Facility Type And Quantity:

2 slot

Feedthru Connection End Type:

600 both ends single combination

Feedthru Terminal Quantity:

6 single combination

Terminal Pattern Arrangement:

Single row

Terminal Design:

Vertical feedthru

Material:

Plastic polyester board and glass fiber board

Material Specification:

Mil-m-14, type mai-60 military specification single material response board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.