NSN 5940-00-901-4249

Lug Terminal - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5940-00-901-4249

Overall Length: 0.547 inches Overall Width: 0.281 inches Material Thickness: 0.031 inches Maximum Conductor Size Accommodated: 18 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Straight one hole Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility single layer Shift Life: N/a Unit Of Measure: Pemilitarization: No Fig: Auoneho	
Overall Width: 0.281 inches Material Thickness: 0.031 inches Maximum Conductor Size Accommodated: 18 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Straight one hole Mounting Hole Diameter: 0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Overall Length:
0.281 inches Material Thickness: 0.031 inches Maximum Conductor Size Accommodated: 18 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Straight one hole Mounting Hole Diameter: 0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.547 inches
Material Thickness: 0.031 inches Maximum Conductor Size Accommodated: 18 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Straight one hole Mounting Hole Diameter: 0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Overall Width:
0.031 inches Maximum Conductor Size Accommodated: 18 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Straight one hole Mounting Hole Diameter: 0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.281 inches
Maximum Conductor Size Accommodated: 18 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Straight one hole Mounting Hole Diameter: 0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Material Thickness:
18 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Straight one hole Mounting Hole Diameter: 0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.031 inches
Electrical Insulation Feature: Uninsulated Mounting Method Style: Straight one hole Mounting Hole Diameter: 0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Maximum Conductor Size Accommodated:
Uninsulated Mounting Method Style: Straight one hole Mounting Hole Diameter: 0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	18 awg
Mounting Method Style: Straight one hole Mounting Hole Diameter: 0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Electrical Insulation Feature:
Straight one hole Mounting Hole Diameter: 0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Uninsulated
Mounting Hole Diameter: 0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Mounting Method Style:
0.173 inches Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Straight one hole
Mounting Facility Thickness: 0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	Mounting Hole Diameter:
0.031 inches Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.173 inches
Basic Shape Style: Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Mounting Facility Thickness:
Crimp Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: 0.140 inches Material: Copper mounting facility Surface Treatment: Copper mounting facility single layer Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.031 inches
Conductor Accommodation Type: Straight barrel single end Distance From Mounting Hole Center To Mounting End: Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Hole Center To Mounting End: Material: Copper mounting facility Hole Center To Mounting End: Material: Copper mounting facility Hole Center To Mounting End: Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Basic Shape Style:
Straight barrel single end Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Crimp
Distance From Mounting Hole Center To Mounting End: 0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Conductor Accommodation Type:
0.140 inches Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Straight barrel single end
Material: Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Distance From Mounting Hole Center To Mounting End:
Copper mounting facility Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.140 inches
Surface Treatment: Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Tin mounting facility single layer Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Copper mounting facility
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
N/a Unit Of Measure: Demilitarization: No Fiig:	Tin mounting facility single layer
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
4006b0	Fiig:
A00000	A006b0