## NSN 5940-00-916-2800

Feedthru Terminal - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-916-2800

| Occasil Height  |
|---|
| Overall Height:   |
| 1.102 inches  |
| Overall Diameter:   |
| 0.312 inches  |
| Largest Diameter:   |
| 0.182 inches all ends   |
| Turret Minor Diameter:  |
| 0.125 inches all ends   |
| Electrical Insulation Feature:  |
| Uninsulated   |
| Mounting Method Style:  |
| Swage   |
| Minor Bushing Length:   |
| 0.165 inches  |
| Swage Depth:  |
| 0.030 inches  |
| Swage Outside Diameter:   |
| 0.312 inches  |
| Basic Shape Style:  |
| Nontubular round  |
| Conductor Accommodation Type:   |
| Double turret all ends  |
| First End Terminal Length:  |
| 0.468 inches  |
| Second End Terminal Length:   |
| 0.437 inches  |
| Material:   |
| Copper alloy  |
| Material Specification:   |
| Qq-b-626, 1/2h federal specification single material response conductor accommodation |
| Precious Material And Location:   |
| O/a external surfaces silver and o/a external surfaces gold                           |
| Precious Material:  |
| Silver and gold   |
| Surface Treatment:  |
| Silver first layer  |
| Surface Treatment Specification:  |
| Qq-s-635, type 2 federal specification 1st treatment response first layer             |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5940-00-916-2800

Feedthru Terminal - Page 2 of 2



| _  |   |   |   |   |   |     |    |   |   |  |
|----|---|---|---|---|---|-----|----|---|---|--|
| וו | 0 | m | ш | м | 2 | iza | 31 | ^ | n |  |
|    |   |   |   |   |   |     |    |   |   |  |

No

Fiig:

A006b0

Mil-std (military Standard):

Mil-g-45204 spec.