NSN 5940-00-926-9820

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-926-9820

| Mounting Hole Diameter: |
|---|
| 0.175 inches |
| Dielectric Withstanding Voltage In Volts: |
| 3.3 |
| Body Style: |
| Barrier type |
| Terminal Row Quantity: |
| 1 |
| Center To Center Distance Between Terminals: |
| 0.438 inches |
| Board Construction: |
| Hollow construction without insulated strip |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.062 inches |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: |
| 0.188 inches |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: |
| 0.156 inches |
| Boardlength: |
| 3.375 inches |
| Boardwidth: |
| 0.688 inches |
| Boardheight: |
| 0.875 inches |
| Board Height Excluding Terminals: |
| 0.500 inches |
| Base Thickness: |
| 0.312 inches |
| Current Rating In Amps: |
| 20.0 |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Feedthru Connection End Type: |
| 857 fourth combination both ends |
| Feedthru Terminal Quantity: |
| 6 single combination |
| Terminal Pattern Arrangement: |
| Single row |
| Terminal Design: |
| Vertical feedthru |
| Material: |
| Plastic phenolic board |

NSN 5940-00-926-9820

Terminal Board - Page 2 of 2



| _ | | - | _ | | | | - |
|---|----|-----|-----|----|-----|-----|-----|
| - | 11 | fac | _ I | rΔ | 2†I | mai | nt. |
| | | | | | | | |

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0