

View Online at <https://aerobasegroup.com/nsn/5940-00-949-3106>

Mounting Hole Diameter:

0.175 inches

Dielectric Withstanding Voltage In Volts:

1100.0

Body Style:

Barrier type

Terminal Row Quantity:

1

Center To Center Distance Between Terminals:

0.438 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.062 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.344 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.156 inches

Boardlength:

3.375 inches

Boardwidth:

0.688 inches

Boardheight:

0.500 inches

Board Height Excluding Terminals:

0.500 inches

Base Thickness:

0.312 inches

Current Rating In Amps:

20.0

Mounting Facility Type And Quantity:

2 unthreaded hole

Nonfeedthru Terminal Type:

857 single

Nonfeedthru Terminal Quantity:

6 single

Terminal Pattern Arrangement:

Single row

Terminal Design:

Nonfeedthru

Material:

Plastic diallyl phthalate board and glass fiber board

Material Specification:

Mil-p-19833, type gdi-30f military specification single material response board

Surface Treatment:

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0

Mil-std (military Standard):

Mil-p-19833 spec.