

View Online at <https://aerobasegroup.com/nsn/5940-00-956-8763>

Mounting Hole Diameter:

0.196 inches

Dielectric Withstanding Voltage In Volts:

3400.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.438 inches

Distance Between Terminal Row Centers:

0.421 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

10.531 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.421 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.196 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.156 inches

Boardlength:

10.859 inches

Boardwidth:

1.125 inches

Boardheight:

1.188 inches

Board Height Excluding Terminals:

0.562 inches

Base Thickness:

0.375 inches

Current Rating In Amps:

10.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Feedthru Connection End Type:

F4 15th material response both ends

Terminal Connecting Link Quantity:

23 single

Feedthru Terminal Quantity:

23 single combination

Terminal Connecting Link Type:

1 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked vertical feedthru

Material:

Plastic diallyl phthalate board and glass fiber board

Material Specification:

Mil-p-19833, type gdi-30f military specification single material response board

Surface Treatment:

Nickel terminals and tin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-p-19833 spec.