## NSN 5940-00-983-5962

Grounding Terminal Strip - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5940-00-983-5962

0.004 inches Overall Length: 4.579 inches Overall Height: Between 0.080 inches and 0.090 inches Overall Width: Between 0.060 inches and 0.070 inches Unit Type: Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	0.004 inches Overall Length: 4.579 inches Overall Height: Between 0.080 inches and 0.090 inches Overall Width: Between 0.060 inches and 0.070 inches Unit Type: Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Hardened Shelf Life: N/a	Overall Depth:
Overall Length:4.579 inchesOverall Height:Between 0.080 inches and 0.090 inchesOverall Width:Between 0.060 inches and 0.070 inchesUnit Type:AngleMounting Method:Any acceptableWire Accommodation Quantity:50Wire Accommodation Size:0.060 inch diameter of holesMaterial:Copper-beryllium alloy, qq-c-533, condition aMaterial:Copper-beryllium alloy, qq-c-533, condition aNuclear Hardness Critical Feature:HardenedShelf Life:N/aUnit Of Measure:	Overall Length:4.579 inchesOverall Height:Between 0.080 inches and 0.090 inchesOverall Width:Between 0.060 inches and 0.070 inchesUnit Type:AngleMounting Method:Any acceptableWire Accommodation Quantity:50Wire Accommodation Size:0.060 inch diameter of holesMaterial:Copper-beryllium alloy, qq-c-533, condition aMaterial:Copper-beryllium alloy, qq-c-533, condition aMaterial:Muclear Hardness Critical Feature:HardenedShelf Life:N/aUnit Of Measure:Demilitarization:No	
4.579 inches Overall Height: Between 0.080 inches and 0.090 inches Overall Width: Between 0.060 inches and 0.070 inches Unit Type: Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Hardened Shelf Life: N/a Unit Of Measure:	4.579 inches Overall Height: Between 0.080 inches and 0.090 inches Overall Width: Between 0.060 inches and 0.070 inches Unit Type: Angle Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:  Demilitarization:	Overall Length:
Between 0.080 inches and 0.090 inches Overall Width: Between 0.060 inches and 0.070 inches Unit Type: Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Between 0.080 inches and 0.090 inches Overall Width: Between 0.060 inches and 0.070 inches Unit Type: Angle Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryl	U U
Between 0.080 inches and 0.090 inches Overall Width: Between 0.060 inches and 0.070 inches Unit Type: Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Between 0.080 inches and 0.090 inches Overall Width: Between 0.060 inches and 0.070 inches Unit Type: Angle Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryl	Overall Height:
Between 0.060 inches and 0.070 inches Unit Type: Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Between 0.060 inches and 0.070 inches Unit Type: Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: No	-
Unit Type: Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Unit Type: Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Material: Copper-beryllium alloy, qq-c-533, condition	Overall Width:
Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Angle Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Na	Between 0.060 inches and 0.070 inches
Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Mounting Method: Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Muclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Unit Type:
Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Any acceptable Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure: Demilitarization: No	Angle
Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Wire Accommodation Quantity: 50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Hardened Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Mounting Method:
50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	50 Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material: Naterial: Naterial: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Material:	Any acceptable
Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Wire Accommodation Size: 0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Wire Accommodation Quantity:
0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure: 	0.060 inch diameter of holes Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:  Demilitarization: No	50
Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Material: Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Wire Accommodation Size:
Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure: 	Copper-beryllium alloy, qq-c-533, condition a Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:  Demilitarization: No	0.060 inch diameter of holes
Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Material: Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Material:
Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure: 	Copper-beryllium alloy, qq-c-533, condition a Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Copper-beryllium alloy, qq-c-533, condition a
Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:	Nuclear Hardness Critical Feature: Hardened Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Material:
Hardened Shelf Life: N/a Unit Of Measure:	Hardened Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Copper-beryllium alloy, qq-c-533, condition a
Shelf Life: N/a Unit Of Measure: 	Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Nuclear Hardness Critical Feature:
N/a Unit Of Measure: 	N/a Unit Of Measure:  Demilitarization: No	Hardened
Unit Of Measure:	Unit Of Measure:  Demilitarization: No	Shelf Life:
	 Demilitarization: No	N/a
	<b>Demilitarization:</b> No	Unit Of Measure:
	No	-
Demilitarization:		Demilitarization:
No	Fiig:	No
Fiig:		Fiig:
T174-b	Т174-b	Т174-b