

View Online at <https://aerobasegroup.com/nsn/5940-00-983-6078>

Mounting Hole Diameter:

0.171 inches

Dielectric Withstanding Voltage In Volts:

3000.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.375 inches

Distance Between Terminal Row Centers:

0.312 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.141 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.312 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.282 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.141 inches

Boardlength:

7.438 inches

Boardwidth:

0.875 inches

Boardheight:

0.922 inches

Board Height Excluding Terminals:

0.484 inches

Base Thickness:

0.328 inches

Current Rating In Amps:

7.5

Mounting Facility Type And Quantity:

4 unthreaded hole

Feedthru Connection End Type:

F4 15th material response both ends

Terminal Connecting Link Quantity:

18 single

Feedthru Terminal Quantity:

18 single combination

Terminal Connecting Link Type:

1 single

Terminal Pattern Arrangement:

Single row

Terminal Design:

Feedthru

Material:

Plastic diallyl phthalate board and glass fiber board

Material Specification:

Mil-p-19833, type gdi-30f military specification single material response board

Surface Treatment:

Tin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-p-19833 spec.