## NSN 5940-00-983-6095

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-983-6095

	nting Hole Diameter:
	3 inches
Diele	ectric Withstanding Voltage In Volts:
3400	
Body	y Style:
Barri	ier type
Tern	ninal Row Quantity:
2	
Cent	ter To Center Distance Between Terminals:
0.43	8 inches
Dista	ance Between Terminal Row Centers:
0.42	1 inches
Boar	rd Construction:
Hollo	ow construction without insulated strip
Cent	ter To Center Distance Between Mounting Facilities Parallel To Length:
8.32	8 inches
Cent	ter To Center Distance Between Mounting Facilities Parallel To Width:
0.42	1 inches
Dista	ance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:
0.35	2 inches
Dista	ance From Left Edge Of Terminal Board To Center Of First Mounting Facility:
0.15	6 inches
Boar	rdlength:
8.65	6 inches
Boai	rdwidth:
1.12	5 inches
Boar	rdheight:
0.57	8 inches
Boar	rd Height Excluding Terminals:
0.57	8 inches
Base	e Thickness:
0.39	1 inches
Curr	ent Rating In Amps:
20.0	
Mou	nting Facility Type And Quantity:
4 uni	threaded hole
Tern	ninal Connecting Link Quantity:
18 si	ingle
Non	feedthru Terminal Type:
857 :	single
Tern	ninal Connecting Link Type:
1 sin	gle

## NSN 5940-00-983-6095

Terminal Board - Page 2 of 2



Nonfeedthru Terminal Quantity:

18 single

**Terminal Pattern Arrangement:** 

Multi-row

**Terminal Design:** 

Linked nonfeedthru

Material:

Plastic board

Surface Treatment:

Nickel terminals

Surface Treatment Specification:

Qq-n-290, class 1, type 8 federal specification single treatment response terminals

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A011b0