NSN 5940-00-983-6096

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-983-6096

| view Offilite at https://aerobasegroup.com/nsi//0540-00-505-0050 |
|---|
| Mounting Hole Diameter: |
| 0.203 inches |
| Dielectric Withstanding Voltage In Volts: |
| 3400.0 |
| Body Style: |
| Barrier type |
| Terminal Row Quantity: |
| 2 |
| Center To Center Distance Between Terminals: |
| 0.438 inches |
| Distance Between Terminal Row Centers: |
| 0.421 inches |
| Board Construction: |
| Solid construction |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 9.219 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.421 inches |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: |
| 0.352 inches |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: |
| 0.156 inches |
| Boardlength: |
| 9.547 inches |
| Boardwidth: |
| 1.125 inches |
| Boardheight: |
| 0.578 inches |
| Board Height Excluding Terminals: |
| 0.578 inches |
| Base Thickness: |
| 0.391 inches |
| Current Rating In Amps: |
| 20.0 |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Terminal Connecting Link Quantity: |
| 20 single |
| Nonfeedthru Terminal Type: |
| 857 single |
| Terminal Connecting Link Type: |

1 single

NSN 5940-00-983-6096 Terminal Board - Page 2 of 2



| Nonfeedthru Terminal Quantity: |
|---|
| 20 single |
| Terminal Pattern Arrangement: |
| Multi-row |
| Terminal Design: |
| Linked nonfeedthru |
| Material: |
| Plastic diallyl phthalate board |
| Surface Treatment: |
| Nickel terminals or tin alloy terminals |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A011b0