

View Online at <https://aerobasegroup.com/nsn/5940-00-983-6096>

**Mounting Hole Diameter:**

0.203 inches

**Dielectric Withstanding Voltage In Volts:**

3400.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.438 inches

**Distance Between Terminal Row Centers:**

0.421 inches

**Board Construction:**

Solid construction

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

9.219 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.421 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.352 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.156 inches

**Boardlength:**

9.547 inches

**Boardwidth:**

1.125 inches

**Boardheight:**

0.578 inches

**Board Height Excluding Terminals:**

0.578 inches

**Base Thickness:**

0.391 inches

**Current Rating In Amps:**

20.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Terminal Connecting Link Quantity:**

20 single

**Nonfeedthru Terminal Type:**

857 single

**Terminal Connecting Link Type:**

1 single

**Nonfeedthru Terminal Quantity:**

20 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Linked nonfeedthru

**Material:**

Plastic diallyl phthalate board

**Surface Treatment:**

Nickel terminals or tin alloy terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0