## NSN 5940-00-983-6112

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-00-983-6112

Mounting Hole Diameter:	
0.221 inches	
Dielectric Withstanding Voltage In Volts:	
4000.0	
Body Style:	
Barrier type	
Terminal Row Quantity:	
2	
Center To Center Distance Between Terminals:	
0.562 inches	
Distance Between Terminal Row Centers:	
0.500 inches	
Board Construction:	
Hollow construction without insulated strip	
Center To Center Distance Between Mounting Facilities Parallel T	o Length:
10.141 inches	
Center To Center Distance Between Mounting Facilities Parallel T	o Width:
0.500 inches	
Distance From Bottom Edge Of Terminal Board To Center Of Mou	Inting Hole:
0.219 inches	
Distance From Left Edge Of Terminal Board To Center Of First Mo	ounting Facility:
0.203 inches	
Boardlength:	
10.562 inches	
Boardwidth:	
1.312 inches	
Boardheight:	
0.688 inches	
Board Height Excluding Terminals:	
0.688 inches	
Base Thickness:	
0.438 inches	
Current Rating In Amps:	
30.0	
Mounting Facility Type And Quantity:	
4 unthreaded hole	
Terminal Connecting Link Quantity:	
17 single	
Nonfeedthru Terminal Type:	
857 single	
Terminal Connecting Link Type:	
1 single	

## NSN 5940-00-983-6112

Terminal Board - Page 2 of 2



Nonfeedthru Terminal Quantity: 17 single **Terminal Pattern Arrangement:** Multi-row **Terminal Design:** Linked nonfeedthru Material: Plastic diallyl phthalate board and glass fiber board **Material Specification:** Mil-p-19833, type gdi-30f military specification single material response board **Surface Treatment:** Nickel terminals Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

Fiig:

---

A011b0

Mil-std (military Standard):

Mil-p-19833 spec.