

View Online at <https://aerobasegroup.com/nsn/5940-00-983-6132>

Mounting Hole Diameter:

0.203 inches

Dielectric Withstanding Voltage In Volts:

3400.0

Body Style:

Barrier type

Terminal Row Quantity:

1

Center To Center Distance Between Terminals:

0.438 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.266 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.421 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.352 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.156 inches

Boardlength:

5.594 inches

Boardwidth:

1.125 inches

Boardheight:

1.203 inches

Board Height Excluding Terminals:

0.578 inches

Base Thickness:

0.391 inches

Current Rating In Amps:

10.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Feedthru Connection End Type:

F4 15th material response both ends

Terminal Connecting Link Quantity:

11 single

Feedthru Terminal Quantity:

11 single combination

Terminal Connecting Link Type:

1 single

Terminal Pattern Arrangement:

Single row

Terminal Design:

Feedthru

Material:

Plastic diallyl phthalate board and glass fiber board

Material Specification:

Mil-p-19833, type gdi-30f military specification single material response board

Surface Treatment:

Nickel terminals and tin terminals

Surface Treatment Specification:

Qq-n-290, class 1, type 8 federal specification 1st treatment response terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-p-19833 spec.