

View Online at <https://aerobasegroup.com/nsn/5940-00-983-6146>

Mounting Hole Diameter:

0.228 inches

Dielectric Withstanding Voltage In Volts:

4000.0

Terminal Row Quantity:

1

Center To Center Distance Between Terminals:

0.562 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.203 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.406 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.203 inches

Boardlength:

6.625 inches

Boardwidth:

1.312 inches

Boardheight:

1.328 inches

Board Height Excluding Terminals:

0.703 inches

Base Thickness:

0.453 inches

Current Rating In Amps:

15.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Feedthru Connection End Type:

F4 15th material response both ends

Terminal Connecting Link Quantity:

10 single

Feedthru Terminal Quantity:

10 single combination

Terminal Connecting Link Type:

1 single

Terminal Pattern Arrangement:

Single row

Terminal Design:

Feedthru

Material:

Plastic board

Surface Treatment:

Nickel terminals and tin terminals

Surface Treatment Specification:

Qq-n-290, class 1, type 8 federal specification 1st treatment response terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0