

View Online at <https://aerobasegroup.com/nsn/5940-00-983-6150>

**Mounting Hole Diameter:**

0.221 inches

**Dielectric Withstanding Voltage In Volts:**

4000.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.562 inches

**Distance Between Terminal Row Centers:**

0.500 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

8.453 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.500 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.218 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.203 inches

**Boardlength:**

8.875 inches

**Boardwidth:**

1.312 inches

**Boardheight:**

1.312 inches

**Board Height Excluding Terminals:**

0.688 inches

**Base Thickness:**

0.438 inches

**Current Rating In Amps:**

15.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Feedthru Connection End Type:**

F4 15th material response both ends

**Terminal Connecting Link Quantity:**

14 single

**Feedthru Terminal Quantity:**

14 single combination

**Terminal Connecting Link Type:**

1 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Linked vertical feedthru

**Material:**

Plastic diallyl phthalate board and glass fiber board

**Material Specification:**

Mil-p-19833, type gdi-30f military specification single material response board

**Surface Treatment:**

Nickel terminals and tin terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0

**Mil-std (military Standard):**

Mil-p-19833 spec.