

View Online at <https://aerobasegroup.com/nsn/5940-01-011-7507>

Dielectric Withstanding Voltage In Volts:

1500.0

Body Style:

Barrier type

Mounting Slot Length:

0.188 inches

Mounting Slot Width:

0.150 inches

Terminal Row Quantity:

1

Center To Center Distance Between Terminals:

0.312 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.312 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.219 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.156 inches

Boardlength:

2.625 inches

Boardwidth:

0.437 inches

Boardheight:

0.489 inches

Board Height Excluding Terminals:

0.375 inches

Base Thickness:

0.250 inches

Current Rating In Amps:

25.0

Mounting Facility Type And Quantity:

2 slot

Nonfeedthru Terminal Type:

600 single

Nonfeedthru Terminal Quantity:

6 single

Terminal Pattern Arrangement:

Single row

Terminal Design:

Nonfeedthru

Material:

Plastic polyester board and glass fiber board

Material Specification:

Mil-m-14, type mai-60 military specification single material response board

Departure From Cited Document:

Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control no.

Me2002a, line no. 0016

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.