

View Online at <https://aerobasegroup.com/nsn/5940-01-011-7507>

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Body Style:**

Barrier type

**Mounting Slot Length:**

0.188 inches

**Mounting Slot Width:**

0.150 inches

**Terminal Row Quantity:**

1

**Center To Center Distance Between Terminals:**

0.312 inches

**Board Construction:**

Solid construction

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.312 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.219 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.156 inches

**Boardlength:**

2.625 inches

**Boardwidth:**

0.437 inches

**Boardheight:**

0.489 inches

**Board Height Excluding Terminals:**

0.375 inches

**Base Thickness:**

0.250 inches

**Current Rating In Amps:**

25.0

**Mounting Facility Type And Quantity:**

2 slot

**Nonfeedthru Terminal Type:**

600 single

**Nonfeedthru Terminal Quantity:**

6 single

**Terminal Pattern Arrangement:**

Single row

**Terminal Design:**

Nonfeedthru

**Material:**

Plastic polyester board and glass fiber board

**Material Specification:**

Mil-m-14, type mai-60 military specification single material response board

**Departure From Cited Document:**

Special requirements for nuclear propulsion plant equipment contained in individual repair parts ordering data instrumentation control no.

Me2002a, line no. 0016

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0

**Mil-std (military Standard):**

Mil-m-14 spec.