

View Online at <https://aerobasegroup.com/nsn/5940-01-022-5461>

Mounting Hole Diameter:

0.175 inches

Dielectric Withstanding Voltage In Volts:

1100.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.438 inches

Distance Between Terminal Row Centers:

0.422 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.812 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.422 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.352 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.156 inches

Boardlength:

5.125 inches

Boardwidth:

1.562 inches

Boardheight:

0.500 inches

Board Height Excluding Terminals:

0.500 inches

Base Thickness:

0.312 inches

Current Rating In Amps:

20.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Feedthru Connection End Type:

F9 15th material response both ends

Feedthru Terminal Quantity:

10 single combination

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Feedthru

Material:

Copper alloy terminals

Surface Treatment:

Nickel terminals and tin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0