

View Online at <https://aerobasegroup.com/nsn/5940-01-024-2466>

Mounting Hole Diameter:

0.175 inches

Dielectric Withstanding Voltage In Volts:

1100.0

Body Style:

Barrier type

Terminal Row Quantity:

1

Center To Center Distance Between Terminals:

0.438 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.938 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.344 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.156 inches

Boardlength:

4.250 inches

Boardwidth:

0.688 inches

Boardheight:

0.765 inches

Board Height Excluding Terminals:

0.500 inches

Base Thickness:

0.312 inches

Current Rating In Amps:

20.0

Mounting Facility Type And Quantity:

2 unthreaded hole

Feedthru Connection End Type:

645 both ends single combination

Feedthru Terminal Quantity:

8 single combination

Terminal Pattern Arrangement:

Single row

Terminal Design:

Feedthru

Special Features:

Kulka electric corporation 601 jumpers added on terminal 1 and 2, 3 and 4

Material:

Plastic phenolic board

Surface Treatment:

Tin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0