

View Online at <https://aerobasegroup.com/nsn/5940-01-027-3074>

**Dielectric Withstanding Voltage In Volts:**

10400.0

**Body Style:**

Sectional

**Mounting Slot Length:**

0.375 inches

**Mounting Slot Width:**

0.218 inches

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

1.000 inches

**Distance Between Terminal Row Centers:**

1.250 inches

**Board Construction:**

Hollow construction with insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

10.687 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.000 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.687 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.375 inches

**Boardlength:**

11.187 inches

**Boardwidth:**

2.500 inches

**Boardheight:**

1.875 inches

**Current Rating In Amps:**

225.0

**Mounting Facility Type And Quantity:**

4 slot

**Terminal Connecting Link Quantity:**

4 single

**Nonfeedthru Terminal Type:**

846 single

**Terminal Connecting Link Type:**

1 single

**Nonfeedthru Terminal Quantity:**

4 single

**Terminal Pattern Arrangement:**

Multi-row staggered

**Terminal Design:**

Linked nonfeedthru

**Special Features:**

Nickel plated brass terminal bar with 3/8 in plated hex-head steel; screw, 225amps/600v wire up to 4/0 awg

**Material:**

Plastic phenolic board

**Material Specification:**

Mil-t-55164, type 8tb10 military specification single material response board

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0

**Mil-std (military Standard):**

Mil-t-55164 spec.