NSN 5940-01-027-5922

Feedthru Terminal - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-01-027-5922

| Overall Height: |
|---|
| 0.670 inches |
| Overall Diameter: |
| 0.063 inches |
| Largest Diameter: |
| 0.053 inches first end |
| Largest Width: |
| 0.025 inches second end |
| Turret Minor Diameter: |
| 0.038 inches first end |
| Electrical Insulation Feature: |
| Uninsulated |
| Mounting Method Style: |
| Press fit knurl |
| Minor Bushing Diameter: |
| 0.058 inches |
| Major Bushing Diameter: |
| 0.063 inches |
| Minor Bushing Length: |
| 0.055 inches |
| Basic Shape Style: |
| Nontubular round |
| Conductor Accommodation Type: |
| Square pin second end |
| First End Terminal Length: |
| 0.090 inches |
| Second End Terminal Length: |
| 0.470 inches |
| Material: |
| Copper alloy 360 mounting facility |
| Material Specification: |
| Qq-b-626, 1/2h federal specification single material response mounting facility |
| Precious Material And Location: |
| O/a surfaces gold |
| Precious Material And Weight: |
| 0.040 gold grains, troy |
| Precious Material: |
| Gold |
| Surface Treatment: |
| Gold mounting facility single layer |

Mil-g-45204, type 2 military specification single treatment response mounting facility single layer

Surface Treatment Specification:

NSN 5940-01-027-5922

Feedthru Terminal - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |
| Fiig: |

Mil-std (military Standard): Mil-g-45204 spec.