

View Online at <https://aerobasegroup.com/nsn/5940-01-031-6354>

**Dielectric Withstanding Voltage In Volts:**

600.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.437 inches

**Distance Between Terminal Row Centers:**

0.812 inches

**Board Construction:**

Constructed of interlocking pieces

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.062 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.375 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.250 inches

**Boardlength:**

4.125 inches

**Boardwidth:**

1.750 inches

**Boardheight:**

1.406 inches

**Board Height Excluding Terminals:**

1.406 inches

**Base Thickness:**

0.625 inches

**Mounting Facility Type And Quantity:**

4 threaded hole

**Features Provided:**

Marker strip

**Nonfeedthru Terminal Type:**

871 single

**Nonfeedthru Terminal Quantity:**

5 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Nonfeedthru

**Special Features:**

Tb1, ti 6850.13, instruction book, visual approach slope indicator system (vasi-4), pg 8-3, sepc0 div

**Material:**

Plastic board

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0