NSN 5940-01-054-5466

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-01-054-5466

| Mounting Hole Diameter: |
|---|
| 0.125 inches |
| Dielectric Withstanding Voltage In Volts: |
| 1000.0 |
| Body Style: |
| Barrier type |
| Terminal Row Quantity: |
| 2 |
| Center To Center Distance Between Terminals: |
| 0.250 inches |
| Distance Between Terminal Row Centers: |
| 0.250 inches |
| Board Construction: |
| Solid construction |
| Terminal Facility Quantity: |
| 12 |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.250 inches |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: |
| 0.188 inches |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: |
| 0.125 inches |
| Boardlength: |
| 3.500 inches |
| Boardwidth: |
| 0.625 inches |
| Boardheight: |
| 0.312 inches |
| Board Height Excluding Terminals: |
| 0.312 inches |
| |
| Base Thickness: |
| Base Thickness: 0.093 inches |
| |
| 0.093 inches |
| 0.093 inches Current Rating In Amps: |
| 0.093 inches Current Rating In Amps: 5.0 |
| 0.093 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: |
| 0.093 inches Current Rating In Amps: 5.0 Mounting Facility Type And Quantity: 4 unthreaded hole |

Multi-row

NSN 5940-01-054-5466

Terminal Board - Page 2 of 2



| Term | ıııaı | DES | uii. |
|------|-------|-----|------|
| | | | |

Linked nonfeedthru

Material:

Glass board and plastic alkyd board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0