

View Online at <https://aerobasegroup.com/nsn/5940-01-065-1846>

Mounting Hole Diameter:

0.175 inches

Dielectric Withstanding Voltage In Volts:

1100.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.438 inches

Distance Between Terminal Row Centers:

0.421 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.421 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.344 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.156 inches

Boardlength:

2.938 inches

Boardwidth:

0.688 inches

Boardheight:

0.500 inches

Board Height Excluding Terminals:

0.500 inches

Base Thickness:

0.312 inches

Current Rating In Amps:

20.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

5 single

Nonfeedthru Terminal Type:

860 second

Terminal Connecting Link Type:

1 single

Nonfeedthru Terminal Quantity:

5 second

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Material:

Plastic phenolic board

Surface Treatment:

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0