## NSN 5940-01-068-0492

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-01-068-0492

| Dielectric   | Withstanding Voltage In Volts:   |
|--------------|--|
| 1100.0       |  |
| Body Style   | 9:   |
| Barrier type | 9  |
| Center To    | Center Distance Between Terminals:   |
| 0.375 inche  | es   |
| Board Cor    | nstruction:  |
| Solid const  | ruction  |
| Center To    | Center Distance Between Mounting Facilities Parallel To Length:  |
| 2.625 inche  |  |
| Distance F   | From Bottom Edge Of Terminal Board To Center Of Mounting Hole:   |
| 0.281 inche  | es   |
| Distance F   | From Left Edge Of Terminal Board To Center Of First Mounting Facility:   |
| 0.226 inche  | es a la construcción de la constru<br>La construcción de la construcción d |
| Boardleng    | th:  |
| 3.078 inche  | es   |
| Boardwidt    | h:   |
| 0.562 inche  | es   |
| Boardheig    | ht:  |
| 1.000 inche  | es   |
| Board Heig   | ght Excluding Terminals:   |
| 0.780 inche  | es   |
| Base Thic    | kness:   |
| 0.312 inche  | es   |
| Current Ra   | ating In Amps:   |
| 15.0         |  |
| Mounting     | Facility Type And Quantity:  |
| 2 friction   |  |
| Feedthru (   | Connection End Type:   |
| 857 fourth   | combination first combination  |
| Feedthru 1   | Ferminal Quantity:   |
| 8 single co  | mbination  |
| Terminal F   | Pattern Arrangement:   |
| Single row   |  |
| Terminal D   | Design:  |
| Vertical fee | edthru   |
| Special Fe   | atures:  |
| Speed nuts   | s 2 furnished per terminal board stainless steel (1/2 hard)  |
| Material:    |  |
| Plastic phe  | nolic board  |
| Shelf Life:  |  |
| N/a          |  |

## NSN 5940-01-068-0492

Terminal Board - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A011b0

