

View Online at <https://aerobasegroup.com/nsn/5940-01-085-3892>

Mounting Hole Diameter:

0.160 inches

Dielectric Withstanding Voltage In Volts:

3000.0

Body Style:

Barrier type

Terminal Row Quantity:

1

Center To Center Distance Between Terminals:

0.375 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

11.641 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.312 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.281 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.141 inches

Boardlength:

11.907 inches

Boardwidth:

0.875 inches

Boardheight:

0.484 inches

Board Height Excluding Terminals:

0.484 inches

Base Thickness:

0.328 inches

Current Rating In Amps:

7.5

Mounting Facility Type And Quantity:

4 unthreaded hole

Feedthru Connection End Type:

F6 15th material response both ends

Feedthru Terminal Quantity:

2 single combination

Terminal Pattern Arrangement:

Single row

Terminal Design:

Feedthru

- Material:**
Plastic diallyl phthalate board and glass fiber board
- Material Specification:**
Qq-b-613, comp 11 federal specification single material response terminals
- Surface Treatment:**
Solder terminals or tin terminals
- Test Data Document:**
81349-mil-t-55164 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
- Shelf Life:**
N/a
- Unit Of Measure:**
--
- Demilitarization:**
No
- Fig:**
A011b0
- Mil-std (military Standard):**
Mil-p-19833 spec.