NSN 5940-01-090-6348

Feedthru Terminal - Page 1 of 2

Overall Height: 0.303 inches

Overall Diameter:

Thru-hole Diameter:

Largest Diameter: 0.090 inches first end

0.172 inches

0.030 inches



View Online at https://aerobasegroup.com/nsn/5940-01-090-6348

Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Cq-b-626 federal specification single material response except insulation single layer Sheff Life: N/a Microson Method Style: Press fit Minor Bushing Diameter: 0.172 inches Major Bushing Diameter: 0.172 inches Minor Bushing Length: 0.100 inches Major Bushing Length: 0.040 inches Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Cq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Sheff Life: N/a	Turret Minor Diameter:
Insulating mounting bushing Mounting Method Style: Press fit Minor Bushing Diameter: 0.148 inches Major Bushing Diameter: 0.172 inches Minor Bushing Length: 0.100 inches Major Bushing Length: 0.100 inches Major Bushing Length: 0.040 inches Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation single layer Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Milt-t-10727 military specification single treatment response except insulation single layer Shelf Life:	0.060 inches first end
Mounting Method Style: Press fit Minor Bushing Diameter: 0.148 inches Major Bushing Diameter: 0.172 inches Minor Bushing Length: 0.100 inches Major Bushing Length: 0.040 inches Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Electrical Insulation Feature:
Press fit Minor Bushing Diameter: 0.148 inches Major Bushing Diameter: 0.172 inches Minor Bushing Length: 0.100 inches Major Bushing Length: 0.040 inches Major Bushing Length: 0.040 inches Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Insulating mounting bushing
Minor Bushing Diameter: 0.148 inches Major Bushing Diameter: 0.172 inches Minor Bushing Length: 0.100 inches Major Bushing Length: 0.040 inches Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification single treatment response except insulation single layer Shelf Life:	Mounting Method Style:
0.148 inches Major Bushing Diameter: 0.172 inches Minor Bushing Length: 0.100 inches Major Bushing Length: 0.040 inches Major Bushing Length: 0.040 inches Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Press fit
Major Bushing Diameter: 0.172 inches Minor Bushing Length: 0.100 inches Major Bushing Length: 0.040 inches Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Minor Bushing Diameter:
Minor Bushing Length: 0.100 inches Major Bushing Length: 0.040 inches Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification single treatment response except insulation single layer Shelf Life:	0.148 inches
Minor Bushing Length: 0.100 inches Major Bushing Length: 0.040 inches Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Major Bushing Diameter:
Major Bushing Length: 0.040 inches Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	0.172 inches
Major Bushing Length: 0.040 inches Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Minor Bushing Length:
Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	0.100 inches
Identification Code Color: Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Major Bushing Length:
Black Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	0.040 inches
Basic Shape Style: Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Identification Code Color:
Tubular, round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Black
Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Basic Shape Style:
Single turret first end First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Tubular, round
First End Terminal Length: 0.133 inches Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Conductor Accommodation Type:
Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Single turret first end
Second End Terminal Length: 0.030 inches Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	First End Terminal Length:
Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	0.133 inches
Material: Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Second End Terminal Length:
Plastic polytetrafluoroethylene insulation Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	0.030 inches
Material Specification: Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Material:
Qq-b-626 federal specification single material response except insulation Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Plastic polytetrafluoroethylene insulation
Surface Treatment: Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Material Specification:
Tin except insulation single layer Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Qq-b-626 federal specification single material response except insulation
Surface Treatment Specification: Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Surface Treatment:
Mil-t-10727 military specification single treatment response except insulation single layer Shelf Life:	Tin except insulation single layer
Shelf Life:	Surface Treatment Specification:
	Mil-t-10727 military specification single treatment response except insulation single layer
N/a	Shelf Life:
	N/a

NSN 5940-01-090-6348

Feedthru Terminal - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A006b0

Mil-std (military Standard):

Mil-p-19468 spec.