

View Online at <https://aerobasegroup.com/nsn/5940-01-091-3909>

**Terminal Length:**

0.146 inches

**Overall Height:**

0.421 inches

**Overall Diameter:**

0.187 inches

**Largest Diameter:**

0.093 inches single end

**Turret Minor Diameter:**

0.045 inches single end

**Electrical Insulation Feature:**

Insulating mounting bushing

**Mounting Method Style:**

Press fit

**Minor Bushing Diameter:**

0.166 inches

**Major Bushing Diameter:**

0.187 inches

**Minor Bushing Length:**

0.150 inches

**Major Bushing Length:**

0.125 inches

**Identification Code Color:**

Red

**Basic Shape Style:**

Nontubular, round

**Conductor Accommodation Type:**

Double turret single end

**Material:**

Plastic polytetrafluoroethylene insulation

**Material Specification:**

Qq-b-750 federal specification single material response conductor accommodation or qq-b-626 federal specification single material response conductor accommodation or astm b-139 assn standard single material response conductor accommodation or astm b-140 assn standard single material response conductor accommodation

**Surface Treatment:**

Tin conductor accommodation single layer or solder conductor accommodation single layer

**Surface Treatment Specification:**

Mil-t-10727 military specification 1st treatment response conductor accommodation single layer or mil-p-81728 military specification 1st treatment response conductor accommodation single layer or qq-s-571 federal specification 2nd treatment response conductor accommodation single layer

**Test Data Document:**

81349-mil-t-55155/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

**Demilitarization:**

No

**Fiig:**

A006b0

**Mil-std (military Standard):**

Mil-p-19468 spec.