

View Online at <https://aerobasegroup.com/nsn/5940-01-094-6754>

Mounting Hole Diameter:

0.125 inches

Dielectric Withstanding Voltage In Volts:

1000.0

Body Style:

Barrier type

Terminal Row Quantity:

1

Center To Center Distance Between Terminals:

0.250 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.203 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.125 inches

Boardlength:

1.500 inches

Boardwidth:

0.406 inches

Boardheight:

0.421 inches

Board Height Excluding Terminals:

0.312 inches

Base Thickness:

0.218 inches

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

2 unthreaded hole

Feedthru Connection End Type:

F6 15th material response both ends

Feedthru Terminal Quantity:

4 single combination

Terminal Pattern Arrangement:

Single row

Terminal Design:

Overedge feedthru

Material:

Plastic diallyl phthalate board and glass fiber board

Material Specification:

Mil-p-19833, type gdi-30f military specification single material response board

Surface Treatment:

Nickel terminals and tin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-p-19833 spec.