

View Online at <https://aerobasegroup.com/nsn/5940-01-095-1523>

**Mounting Hole Diameter:**

0.125 inches

**Dielectric Withstanding Voltage In Volts:**

1000.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

1

**Center To Center Distance Between Terminals:**

0.250 inches

**Board Construction:**

Hollow construction with insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.750 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.203 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.125 inches

**Boardlength:**

2.000 inches

**Boardwidth:**

0.406 inches

**Boardheight:**

0.312 inches

**Board Height Excluding Terminals:**

0.312 inches

**Base Thickness:**

0.219 inches

**Current Rating In Amps:**

5.0

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Nonfeedthru Terminal Type:**

859 single

**Nonfeedthru Terminal Quantity:**

5 single

**Terminal Pattern Arrangement:**

Single row

**Terminal Design:**

Nonfeedthru

**Material:**

Plastic diallyl phthalate board and glass fiber board

**Material Specification:**

Qq-w-321 federal specification single material response terminals

**Surface Treatment:**

Nickel terminals

**Surface Treatment Specification:**

Qq-n-290 federal specification single treatment response terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0

**Mil-std (military Standard):**

Mil-p-19833 spec.