

View Online at <https://aerobasegroup.com/nsn/5940-01-100-9627>

Mounting Hole Diameter:

0.156 inches

Dielectric Withstanding Voltage In Volts:

1100.0

Body Style:

Barrier type

Terminal Row Quantity:

1

Center To Center Distance Between Terminals:

0.375 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.281 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.141 inches

Boardlength:

2.531 inches

Boardwidth:

0.562 inches

Boardheight:

0.718 inches

Board Height Excluding Terminals:

0.406 inches

Base Thickness:

0.250 inches

Current Rating In Amps:

15.0

Mounting Facility Type And Quantity:

2 unthreaded hole

Feedthru Connection End Type:

F4 15th material response both ends

Feedthru Terminal Quantity:

5 single combination

Terminal Pattern Arrangement:

Single row

Terminal Design:

Overedge feedthru

Material:

Plastic phenolic board and cellulose board

Material Specification:

Mil-m-14, type cfg military specification single material response board

Surface Treatment:

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0

Mil-std (military Standard):

Mil-m-14 spec.