

View Online at <https://aerobasegroup.com/nsn/5940-01-100-9627>

**Mounting Hole Diameter:**

0.156 inches

**Dielectric Withstanding Voltage In Volts:**

1100.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

1

**Center To Center Distance Between Terminals:**

0.375 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.250 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.281 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.141 inches

**Boardlength:**

2.531 inches

**Boardwidth:**

0.562 inches

**Boardheight:**

0.718 inches

**Board Height Excluding Terminals:**

0.406 inches

**Base Thickness:**

0.250 inches

**Current Rating In Amps:**

15.0

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Feedthru Connection End Type:**

F4 15th material response both ends

**Feedthru Terminal Quantity:**

5 single combination

**Terminal Pattern Arrangement:**

Single row

**Terminal Design:**

Overedge feedthru

**Material:**

Plastic phenolic board and cellulose board

**Material Specification:**

Mil-m-14, type cfg military specification single material response board

**Surface Treatment:**

Nickel terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0

**Mil-std (military Standard):**

Mil-m-14 spec.