## NSN 5940-01-104-1077

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-01-104-1077

| ·   |
|---|
| Mounting Hole Diameter:   |
| 0.127 inches  |
| Dielectric Withstanding Voltage In Volts:                                       |
| 1500.0  |
| Body Style:   |
| Strip type  |
| Terminal Row Quantity:  |
| 2   |
| Center To Center Distance Between Terminals:                                    |
| 0.312 inches  |
| Distance Between Terminal Row Centers:  |
| 1.250 inches  |
| Board Construction:   |
| Solid construction  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:       |
| 2.060 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:        |
| 0.625 inches  |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:         |
| 0.180 inches  |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: |
| 0.180 inches  |
| Boardlength:  |
| 2.420 inches  |
| Boardwidth:   |
| 1.610 inches  |
| Board Thickness:  |
| 0.093 inches  |
| Mounting Facility Type And Quantity:  |
| 6 unthreaded hole   |
| Nonfeedthru Terminal Type:  |
| 434 single  |
| Nonfeedthru Terminal Quantity:  |
| 12 single   |
| Terminal Pattern Arrangement:   |
| Multi-row   |
| Terminal Design:  |
| Nonfeedthru   |
| Material:   |
| Plastic epoxy board and cellulose board   |
| Material Specification:   |

Qq-b-626, comp 22 1/2 h federal specification single material response terminals

## NSN 5940-01-104-1077

Terminal Board - Page 2 of 2



| N/a               |
|-------------------|
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
| Fiig:             |
| A011b0            |

Mil-std (military Standard):

Mil-p-18177 spec.

Shelf Life: