

View Online at <https://aerobasegroup.com/nsn/5940-01-109-6744>

Mounting Hole Diameter:

0.170 inches

Dielectric Withstanding Voltage In Volts:

1100.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.375 inches

Distance Between Terminal Row Centers:

0.312 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.312 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.281 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.140 inches

Boardlength:

3.281 inches

Boardwidth:

0.875 inches

Boardheight:

1.031 inches

Board Height Excluding Terminals:

0.406 inches

Base Thickness:

0.250 inches

Current Rating In Amps:

15.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Feedthru Connection End Type:

F4 15th material response both ends

Nonfeedthru Terminal Type:

857 single

Feedthru Terminal Quantity:

7 single combination

Nonfeedthru Terminal Quantity:

7 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Nonfeedthru

Special Features:

Includes 2 barrier jumpers, kulka p/n 600j, located on right end of board

Material:

Plastic phenolic board

Surface Treatment:

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0