

View Online at <https://aerobasegroup.com/nsn/5940-01-112-3110>

**Mounting Hole Diameter:**

0.203 inches

**Dielectric Withstanding Voltage In Volts:**

1700.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.687 inches

**Distance Between Terminal Row Centers:**

0.620 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.620 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.210 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.905 inches

**Boardlength:**

1.406 inches

**Boardwidth:**

1.810 inches

**Boardheight:**

0.750 inches

**Board Height Excluding Terminals:**

0.750 inches

**Base Thickness:**

0.430 inches

**Current Rating In Amps:**

50.0

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Terminal Connecting Link Quantity:**

1 single

**Nonfeedthru Terminal Type:**

857 single

**Terminal Connecting Link Type:**

1 single

**Nonfeedthru Terminal Quantity:**

1 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Linked nonfeedthru

**Special Features:**

Mtg holes are at leftend of terminal board; special requirements for irpod hx

**Material:**

Plastic polyester board and glass fiber board

**Material Specification:**

Mil-m-14, type mai-60 military specification single material response board

**Surface Treatment:**

Nickel terminals

**Reference Number Differentiating Characteristics:**

As differentiated by special features

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0

**Mil-std (military Standard):**

Mil-m-14 spec.