

View Online at <https://aerobasegroup.com/nsn/5940-01-122-7358>

**Mounting Hole Diameter:**

0.125 inches

**Dielectric Withstanding Voltage In Volts:**

1000.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.250 inches

**Distance Between Terminal Row Centers:**

0.250 inches

**Board Construction:**

Solid construction

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.750 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.250 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.188 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.125 inches

**Boardlength:**

2.000 inches

**Boardwidth:**

0.625 inches

**Boardheight:**

0.328 inches

**Board Height Excluding Terminals:**

0.328 inches

**Base Thickness:**

0.218 inches

**Current Rating In Amps:**

5.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Terminal Connecting Link Quantity:**

6 single

**Nonfeedthru Terminal Type:**

857 first

**Terminal Connecting Link Type:**

1 single

**Nonfeedthru Terminal Quantity:**

6 second

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Nonfeedthru

**Material:**

Plastic phenolic board

**Surface Treatment:**

Nickel terminals and tin terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0