

View Online at <https://aerobasegroup.com/nsn/5940-01-128-4530>

**Mounting Hole Diameter:**

0.160 inches

**Dielectric Withstanding Voltage In Volts:**

300.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.375 inches

**Distance Between Terminal Row Centers:**

0.312 inches

**Board Construction:**

Solid construction

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.312 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.282 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.140 inches

**Boardlength:**

3.656 inches

**Boardwidth:**

0.875 inches

**Boardheight:**

0.625 inches

**Board Height Excluding Terminals:**

0.625 inches

**Base Thickness:**

0.250 inches

**Current Rating In Amps:**

20.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Terminal Connecting Link Quantity:**

8 single

**Nonfeedthru Terminal Type:**

650 first

**Terminal Connecting Link Type:**

1 single

**Nonfeedthru Terminal Quantity:**

8 second

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Linked nonfeedthru

**Material:**

Steel terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0