NSN 5940-01-160-6209

Feedthru Terminal - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5940-01-160-6209

Overall Height:
0.385 inches
Overall Diameter:
0.172 inches
Largest Diameter:
0.093 inches all ends
Turret Minor Diameter:
0.040 inches all ends
Electrical Insulation Feature:
Insulating mounting bushing
Mounting Method Style:
Press fit
Minor Bushing Diameter:
0.148 inches
Major Bushing Diameter:
0.172 inches
Minor Bushing Length:
0.100 inches
Major Bushing Length:
0.040 inches
Identification Code Color:
White
White Basic Shape Style:
Basic Shape Style:
Basic Shape Style: Nontubular round
Basic Shape Style: Nontubular round Conductor Accommodation Type:
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length:
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches Second End Terminal Length:
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches Second End Terminal Length: 0.085 inches
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches Second End Terminal Length: 0.085 inches Material:
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches Second End Terminal Length: 0.085 inches Material: Plastic polytetrafluoroethylene mounting facility
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches Second End Terminal Length: 0.085 inches Material: Plastic polytetrafluoroethylene mounting facility Surface Treatment:
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches Second End Terminal Length: 0.085 inches Material: Plastic polytetrafluoroethylene mounting facility Surface Treatment: Tin conductor accommodation single layer
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches Second End Terminal Length: 0.085 inches Material: Plastic polytetrafluoroethylene mounting facility Surface Treatment: Tin conductor accommodation single layer Shelf Life:
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches Second End Terminal Length: 0.085 inches Material: Plastic polytetrafluoroethylene mounting facility Surface Treatment: Tin conductor accommodation single layer Shelf Life: N/a
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches Second End Terminal Length: 0.085 inches Material: Plastic polytetrafluoroethylene mounting facility Surface Treatment: Tin conductor accommodation single layer Shelf Life: N/a
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches Second End Terminal Length: 0.085 inches Material: Plastic polytetrafluoroethylene mounting facility Surface Treatment: Tin conductor accommodation single layer Shelf Life: N/a Unit Of Measure:
Basic Shape Style: Nontubular round Conductor Accommodation Type: Single turret first end First End Terminal Length: 0.160 inches Second End Terminal Length: 0.085 inches Material: Plastic polytetrafluoroethylene mounting facility Surface Treatment: Tin conductor accommodation single layer Shelf Life: N/a Unit Of Measure: Demilitarization: