NSN 5940-01-182-2432

Feedthru Terminal - Page 1 of 2

Overall Height: 0.479 inches

Overall Diameter:

Largest Diameter:

0.172 inches



View Online at https://aerobasegroup.com/nsn/5940-01-182-2432

| 0.058 inches second end | | | | | | |
|---|--|--|--|--|--|--|
| Largest Width: | | | | | | |
| 0.172 inches first end | | | | | | |
| Turret Minor Diameter: | | | | | | |
| 0.050 inches second end | | | | | | |
| Wire Hole Diameter: | | | | | | |
| 0.093 inches first end | | | | | | |
| Electrical Insulation Feature: | | | | | | |
| Insulating mounting bushing | | | | | | |
| Mounting Method Style: | | | | | | |
| Press fit | | | | | | |
| Minor Bushing Diameter: | | | | | | |
| 0.148 inches | | | | | | |
| Major Bushing Diameter: | | | | | | |
| 0.172 inches | | | | | | |
| Minor Bushing Length: | | | | | | |
| 0.070 inches | | | | | | |
| Major Bushing Length: | | | | | | |
| 0.040 inches | | | | | | |
| Dry Flashover Voltage Rating In Volts: | | | | | | |
| 1000.0 | | | | | | |
| Identification Code Color: | | | | | | |
| | | | | | | |
| White | | | | | | |
| White Basic Shape Style: | | | | | | |
| | | | | | | |
| Basic Shape Style: | | | | | | |
| Basic Shape Style: Nontubular round | | | | | | |
| Basic Shape Style: Nontubular round Conductor Accommodation Type: | | | | | | |
| Basic Shape Style: Nontubular round Conductor Accommodation Type: Wire hook first end | | | | | | |
| Basic Shape Style: Nontubular round Conductor Accommodation Type: Wire hook first end First End Terminal Length: | | | | | | |
| Basic Shape Style: Nontubular round Conductor Accommodation Type: Wire hook first end First End Terminal Length: 0.250 inches | | | | | | |
| Basic Shape Style: Nontubular round Conductor Accommodation Type: Wire hook first end First End Terminal Length: 0.250 inches Second End Terminal Length: | | | | | | |
| Basic Shape Style: Nontubular round Conductor Accommodation Type: Wire hook first end First End Terminal Length: 0.250 inches Second End Terminal Length: 0.119 inches | | | | | | |
| Basic Shape Style: Nontubular round Conductor Accommodation Type: Wire hook first end First End Terminal Length: 0.250 inches Second End Terminal Length: 0.119 inches Material: | | | | | | |
| Basic Shape Style: Nontubular round Conductor Accommodation Type: Wire hook first end First End Terminal Length: 0.250 inches Second End Terminal Length: 0.119 inches Material: Plastic polytetrafluoroethylene insulation | | | | | | |
| Basic Shape Style: Nontubular round Conductor Accommodation Type: Wire hook first end First End Terminal Length: 0.250 inches Second End Terminal Length: 0.119 inches Material: Plastic polytetrafluoroethylene insulation Surface Treatment: | | | | | | |
| Basic Shape Style: Nontubular round Conductor Accommodation Type: Wire hook first end First End Terminal Length: 0.250 inches Second End Terminal Length: 0.119 inches Material: Plastic polytetrafluoroethylene insulation Surface Treatment: Lead except insulation first layer | | | | | | |
| Basic Shape Style: Nontubular round Conductor Accommodation Type: Wire hook first end First End Terminal Length: 0.250 inches Second End Terminal Length: 0.119 inches Material: Plastic polytetrafluoroethylene insulation Surface Treatment: Lead except insulation first layer Shelf Life: | | | | | | |

NSN 5940-01-182-2432

Feedthru Terminal - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A006b0