

View Online at <https://aerobasegroup.com/nsn/5940-01-184-0630>

**Mounting Hole Diameter:**

0.265 inches

**Dielectric Withstanding Voltage In Volts:**

2100.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

1.125 inches

**Distance Between Terminal Row Centers:**

0.870 inches

**Board Construction:**

Solid construction

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.870 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.815 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.310 inches

**Boardlength:**

5.125 inches

**Boardwidth:**

2.500 inches

**Boardheight:**

1.370 inches

**Board Height Excluding Terminals:**

1.120 inches

**Base Thickness:**

0.620 inches

**Current Rating In Amps:**

90.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Terminal Connecting Link Quantity:**

3 single

**Nonfeedthru Terminal Type:**

599 single

**Terminal Connecting Link Type:**

1 single

**Nonfeedthru Terminal Quantity:**

3 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Linked nonfeedthru

**Material:**

Plastic diallyl phthalate board and glass fiber board

**Material Specification:**

Mil-p-19833, type gdi-30f military specification single material response board

**Surface Treatment:**

Nickel terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0

**Mil-std (military Standard):**

Mil-p-19833 spec.