NSN 5940-01-278-3166

Lug Terminal - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5940-01-278-3166

Overall Length:0.590 inchesOverall Width:0.250 inchesMaterial Thickness:0.014 inchesMaximum Conductor Size Accommodated:20 awgElectrical Insulation Feature:UninsulatedMounting Method Style:Open slotMounting Tongue Width:0.250 inchesMounting Slot Width:0.144 inchesBasic Shape Style:Solder/solderlessConductor Accommodation Type:Clamping tang ears single endMaterial:Copper alloyShelf Life:N/aPinitiarization:NoFig:A006b0	
Overall Width:0.250 inchesMaterial Thickness:0.014 inchesMaximum Conductor Size Accommodated:20 awgElectrical Insulation Feature:UninsulatedMounting Method Style:Open slotMounting Tongue Width:0.250 inchesMounting Facility Thickness:0.014 inchesMounting Slot Width:0.145 inchesBasic Shape Style:Solder/solderlessConductor Accommodation Type:Clamping tang ears single endMaterial:Copper alloyShelf Life:N/aUnit of Measure:Pemilitarization:NoFiig:	Overall Length:
0.250 inches Material Thickness: 0.014 inches Maximum Conductor Size Accommodated: 20 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Open slot Mounting Tongue Width: 0.250 inches Mounting Facility Thickness: 0.014 inches Mounting Slot Width: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: - Demilitarization: No	0.590 inches
Material Thickness: 0.014 inches Maximum Conductor Size Accommodated: 20 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Open slot Mounting Tongue Width: 0.250 inches Mounting Facility Thickness: 0.014 inches Mounting Slot Width: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Overall Width:
0.014 inches Maximum Conductor Size Accommodated: 20 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Open slot Mounting Tongue Width: 0.250 inches Mounting Facility Thickness: 0.014 inches Mounting Slot Width: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Maximum Conductor Size Accommodated: 20 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Open slot Mounting Tongue Width: 0.250 inches Mounting Facility Thickness: 0.014 inches Mounting Slot Width: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material Thickness:
20 awg Electrical Insulation Feature: Uninsulated Mounting Method Style: Open slot Mounting Tongue Width: 0.250 inches Mounting Facility Thickness: 0.014 inches Mounting Slot Width: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.014 inches
Electrical Insulation Feature: Uninsulated Mounting Method Style: Open slot Mounting Tongue Width: 0.250 inches Mounting Facility Thickness: 0.014 inches Mounting Slot Width: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No	Maximum Conductor Size Accommodated:
Uninsulated Mounting Method Style: Open slot Mounting Tongue Width: 0.250 inches Mounting Facility Thickness: 0.014 inches Mounting Slot Width: 0.145 inches Mounting Slot Width: 0.145 inches Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No	20 awg
Mounting Method Style: Open slot Mounting Tongue Width: 0.250 inches Mounting Facility Thickness: 0.014 inches Mounting Slot Width: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: T Demilitarization: No Fiig:	Electrical Insulation Feature:
Open slotMounting Tongue Width:0.250 inchesMounting Facility Thickness:0.014 inchesMounting Slot Width:0.145 inchesBasic Shape Style:Solder/solderlessConductor Accommodation Type:Clamping tang ears single endMaterial:Copper alloyShelf Life:N/aUnit Of Measure:-NoFig:	Uninsulated
Mounting Tongue Width: 0.250 inches Mounting Facility Thickness: 0.014 inches Mounting Slot Width: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No	Mounting Method Style:
0.250 inches Mounting Facility Thickness: 0.014 inches Mounting Slot Width: 0.145 inches Basic Shape Style: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Open slot
Mounting Facility Thickness: 0.014 inches Mounting Slot Width: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Fig:	Mounting Tongue Width:
0.014 inches Mounting Slot Width: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.250 inches
Mounting Slot Width: 0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Fig:	Mounting Facility Thickness:
0.145 inches Basic Shape Style: Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.014 inches
Basic Shape Style:Solder/solderlessConductor Accommodation Type:Clamping tang ears single endMaterial:Copper alloyShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Mounting Slot Width:
Solder/solderless Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.145 inches
Conductor Accommodation Type: Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Pomilitarization: No	Basic Shape Style:
Clamping tang ears single end Material: Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Solder/solderless
Material:Copper alloyShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Conductor Accommodation Type:
Copper alloy Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Clamping tang ears single end
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
N/a Unit Of Measure: Demilitarization: No Fiig:	Copper alloy
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A006b0	Fiig:
	A006b0