

View Online at <https://aerobasegroup.com/nsn/5940-01-338-7318>

**Mounting Hole Diameter:**

0.171 inches

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.375 inches

**Distance Between Terminal Row Centers:**

0.312 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.422 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.312 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.328 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.141 inches

**Boardlength:**

1.422 inches

**Boardwidth:**

0.922 inches

**Boardheight:**

0.922 inches

**Board Height Excluding Terminals:**

0.484 inches

**Base Thickness:**

0.328 inches

**End Application:**

Dbrite

**Current Rating In Amps:**

7.5

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Feedthru Connection End Type:**

857 fourth combination both ends

**Terminal Connecting Link Quantity:**

2 single

**Feedthru Terminal Quantity:**

2 single combination

**Terminal Connecting Link Type:**

1 single

**Terminal Pattern Arrangement:**

Single row

**Terminal Design:**

Feedthru

**Special Features:**

Temperature range 130 degree, material gpt-30f

**Material:**

Plastic board

**Surface Treatment:**

Nickel terminals and tin terminals

**Surface Treatment Specification:**

Qq-n-290, class 1, type b federal specification 1st treatment response terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0