NSN 5940-01-445-5197

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-01-445-5197

| Mounting Hole Diameter: | | | |
|---|--|--|--|
| 0.203 inches | | | |
| Dielectric Withstanding Voltage In Volts: | | | |
| 3000.0 | | | |
| Body Style: | | | |
| Barrier type | | | |
| Terminal Row Quantity: | | | |
| 2 | | | |
| Center To Center Distance Between Terminals: | | | |
| 0.438 inches | | | |
| Distance Between Terminal Row Centers: | | | |
| 0.421 inches | | | |
| Board Construction: | | | |
| Solid construction | | | |
| Terminal Facility Quantity: | | | |
| 4 | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | | |
| 5.703 inches | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | | | |
| 0.421 inches | | | |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: | | | |
| 0.352 inches | | | |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: | | | |
| 0.156 inches | | | |
| Boardlength: | | | |
| 6.031 inches | | | |
| Boardwidth: | | | |
| 1.125 inches | | | |
| Boardheight: | | | |
| 0.578 inches | | | |
| Board Height Excluding Terminals: | | | |
| 0.578 inches | | | |
| Base Thickness: | | | |
| 0.391 inches | | | |
| Current Rating In Amps: | | | |
| 20.0 | | | |
| Mounting Facility Type And Quantity: | | | |
| 4 unthreaded hole | | | |
| Terminal Pattern Arrangement: | | | |
| Multi-row | | | |
| | | | |

Voltage ratin (): 600 volts

NSN 5940-01-445-5197

Terminal Board - Page 2 of 2



| ΝЛ | ate | ria | |
|-----|-----|------|-----|
| IVI | ale | :110 | II. |

Copper alloy terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0