NSN 5940-01-469-9227

Terminal Board - Page 1 of 2

Mounting Hole Diameter:

0.120 inches



View Online at https://aerobasegroup.com/nsn/5940-01-469-9227

| Dielectric Withstanding Voltage In Volts: |
|---|
| 300.0 |
| Body Style: |
| Barrier type |
| Center To Center Distance Between Terminals: |
| 0.375 inches |
| Board Construction: |
| Solid construction |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.625 inches |
| Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole: |
| 0.312 inches |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: |
| 0.225 inches |
| Boardlength: |
| 3.075 inches |
| Boardwidth: |
| 0.625 inches |
| Boardheight: |
| 0.750 inches |
| Board Height Excluding Terminals: |
| 12.1 millimeters |
| Base Thickness: |
| 11.4 millimeters |
| End Application: |
| Power supply, used on wasp class Ihd |
| Current Rating In Amps: |
| 20.0 |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Terminal Pattern Arrangement: |
| Single row |
| Special Features: |
| Continuous use temp (ul index) 115 degrees c |
| Material: |
| Plastic polypropylene board |
| Surface Treatment: |
| Tin terminals |
| Shelf Life: |
| N/a |

NSN 5940-01-469-9227

Terminal Board - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A011b0