

View Online at <https://aerobasegroup.com/nsn/5940-01-474-7351>

**Mounting Hole Diameter:**

0.171 inches

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.375 inches

**Distance Between Terminal Row Centers:**

0.312 inches

**Board Construction:**

Solid construction

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.312 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.281 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.141 inches

**Boardlength:**

3.312 inches

**Boardwidth:**

0.875 inches

**Boardheight:**

0.484 inches

**Board Height Excluding Terminals:**

0.484 inches

**Base Thickness:**

0.328 inches

**Current Rating In Amps:**

15.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Terminal Pattern Arrangement:**

Multi-row

**Special Features:**

Yb in part number indicates a temperature of 130 degrees centigrade, material for terminal board molding of gpt-30f, color is semi-gloss gray, no. 26307; terminals may be of bronze; terminals have a corrosion resistant finish

**Material:**

Copper alloy terminals

**Surface Treatment:**

Nickel terminals or nickel alloy terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0