

View Online at <https://aerobasegroup.com/nsn/5940-01-482-3316>

Mounting Hole Diameter:

0.174 inches

Dielectric Withstanding Voltage In Volts:

7500.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.438 inches

Distance Between Terminal Row Centers:

0.420 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.187 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.420 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.353 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.157 inches

Boardlength:

2.500 inches

Boardwidth:

1.125 inches

Boardheight:

0.550 inches

Board Height Excluding Terminals:

0.550 inches

Base Thickness:

0.875 inches

End Application:

E.O.S. Alarm panel

Current Rating In Amps:

20.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Pattern Arrangement:

Multi-row

Special Features:

4 terminals ; construction: closed back, feed-thru; material: black thermoplastic board; voltage: 300 volts; recommended wire size: 16-14 awg solid/ stranded; screws: 6/32 steel combo head (phillip/slot); ul flame retardant rating 94v-0

Material:

Plastic board

Surface Treatment:

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0